



BECAUSE
IMPROVEMENT
NEVER
STOPS



DNX 6-50 MZ
PROFESSIONAL
PISTON COMPRESSORS



← As a serious DIYer, you need a professional piston compressor. Because even if you don't use your compressor all the time, when you do, you expect top performance. And that is exactly what the powerful Worthington Creyssensac DNX MZ will give you: a long lifetime of powering more tools with absolutely clean, oil-free air.

Powerful

You get up to 10 bar of pressure, allowing you to use specialized, higher-pressure tools.

Low noise

With sound emissions as low as 60 dB(A), the DNX MZ makes for a comfortable working environment.

Reliable

The DNX MZ comes with an oil-free, direct-driven pump that requires less maintenance to offer you a longer lifetime of dependable performance.

Flexible configurations

With 1 and 2 HP versions and 6L, 24L and 50L vessel configurations, you are guaranteed to find a DNX MZ that meets your specific needs.

Easy to use

The DNX MZ is a true plug-and-play compressor. Thanks to its handy pressure switch, operating it is a breeze.

Safe

The compressor is completely enclosed to protect you from its hot and moving parts.

CHOOSE YOUR DNX MZ

DNX MZ 6L

- Air displacement up to 230 l/min.
- 1 or 2 HP models.
- Up to 10 bar.
- 6L vessel.
- Compact unit with integrated pressure regulator and vessel tucked under the compressor.

DNX MZ 24L & 50L

- Air displacement up to 230 l/min.
- 2 HP.
- Up to 10 bar.
- 24L or 50L vessels.
- Thanks to its sturdy back wheels and ergonomic handle, you can take your larger DNX MZ wherever you need it with minimal effort.



DNX MZ 6L



DNX MZ 24L & 50L

A FIRST-CLASS PUMP



• Oil-free air protects your tools, your jobs, and the environment.



• Large cooling fan ensures optimal heat dissipation.



• Improved noise level thanks to well-balanced pump and reduced vibration level.



• Extremely quiet 1 HP unit with low pump RPM and 4-pole motor.



• Reliable ball bearings extend the compressor's lifetime.

TECHNICAL SPECIFICATIONS

Model	Power		Pressure bar	Pump type	RPM min-1	Air displacement		Vessel L.	Noise dB(A)	Voltage V/ph/Hz	Dimensions L x W x H	Weight KG	Lubri- cation
	HP	kW				l/min	m3/h						
DNX 6 MZ10	1	0.75	10	MZ10	1450	115	6.9	6	60	230/1/50	372 x 307 x 505	19	Oil-free
DNX 6 MZ20	2	1.5	10	MZ20	2900	230	13.8	6	67	230/1/50	372 x 307 x 505	19	Oil-free
DNX 24 MZ20	2	1.5	10	MZ20	2900	230	13.8	24	72	230/1/50	606 x 300 x 610	23	Oil-free
DNX 50 MZ20	2	1.5	10	MZ20	2900	230	13.8	50	72	230/1/50	807 x 385 x 646	31	Oil-free

6999010640